

# PayTec UPT1000F<sup>+</sup>

Full Touch

For any unattended Business needs  
Durable and cost-effective

- + Secure and high performance MCU
- + Secure Linux operating system
- + 3.5" color display with touch screen
- + PCI PTS 5.x, EMV L1 and EMV L2 certified
- + Accepts all payment types

The newly designed **UPT1000F** device offers multifunctional capabilities for your unattended payment needs.

The device is based on a secure Linux platform and has integrated PIN pad, magnetic stripe, chip and contactless card reader functions.



Perfect suitable for:

- |                         |               |                          |
|-------------------------|---------------|--------------------------|
| + Vending               | + Ticketing   | + Multimedia Kiosks      |
| + Public Transportation | + Laundromats | + Self Service Solutions |

unattended Terminal Series<sup>+</sup>



PayTec AG

Vogelsangstrasse 15  
CH-8307 Effretikon

Tel.: +41 (0)52 354 53 00  
Fax: +41 (0) 52 35 53 10

sales@paytec.ch  
www.paytec.ch

# Datasheet<sup>+</sup>

## PayTec UPT1000F

Processor	32-bit Secure Microprocessor running powerful Linux based OS
Memory	256MB/128MB
KeyPad	Virtual Keypad (supports PIN on touch)
Display	3.5" 320 x 480 Pixels Color TFT LCD
Card Reader	<p>Magnet Stripe: ISO 7810, 7811, 7813 Triple Track, Bi-Directional</p> <p>Contact Card User: ISO 7816 ID-1 1.8V/3V/5V T=0, T=1 Contact Card SAM: 2 (upt to 4)</p> <p>Concactless: ISO 14443 Type A, B  ISO 18092 NFC Mifare and Sony FeliCa Working Frequency 13.56MHz</p> <p>Dual SIM</p>
Communication Interface Options	<p>Wire: RS232*3   USB OTG*1  USB Host*2</p> <p>Wireless: 3G/4G   Bluetooth iBeacon   Ethernet</p>
Indicators	Speaker
Power supply	Power Adapter 9V to 34V (MDB series: 9V~48V)@1.5A~0.5A
Dimensions (L x M x H)	106 x 85 x 62 (mm)
Weight	335 g
Environment	<p>Operating Temperature: -20° C to 65° C</p> <p>Storage Temperature: -35° C to 65° C</p> <p>Operating Humidity: 5% to 90% non-condensing</p> <p>Storage Humidity: 5% to 95% non-condensing</p>
IP Ingress Protection	IP 65
IK Shock Protection	IK 10
Approvals Certifications	<p>PCI PTS 5.x   EMV L1/L2   payWave   PayPass   ExpressPay D-PAS   Interac Flash</p> <p>J-Speedy   FeliCa   UnionPay UICS   TQM   PBOC L1/L2</p>
ECR interface	KIT, MDB, ZVT, ValuePOS, ccTalk, Pepper