

## Technische Daten

### PayTec UPT1000F (Typ: UPT1000F-C-PCI-35-CL-256-4S)

Artikel-Nummer: PT206493

Processor	32-bit Secure Microprocessor running powerful Linux based OS
Memory	256MB/128MB
KeyPad	Virtual Keypad (supports PIN on touch)
Display	3.5" 320 x 480 Pixels Color TFT LCD
Card Reader	Magstripe: ISO 7810, 7811, 7813 Triple Track, Bi-Directional Contact Card User: ISO 7816 ID-1 1.8V/3V/5V T=0, T=1 Contact Card SAM: 2 (up to 4) Contactless: ISO 14443 Type A, B   ISO 18092 NFC Mifare and Sony FeliCa Working Frequency 13.56MHz
Communication Interface Options	Wire: RS232*3   USB OTG*1   USB Host*2 Ethernet
Indicators	Speaker
Power supply	Power Adapter 9V to 34V (MDB series: 9V~48V) @1.5A~0.5A
Dimensions (L x M x H)	106 x 85 x 62 (mm)
Weight	335 g
Environment	Operating Temperature: -20° C to 65° C Storage Temperature: -35° C to 65° C Operating Humidity: 5% to 90% non-condensing Storage Humidity: 5% to 95% non-condensing
IP Ingress Protection	IP 54
IK Shock Protection	IK 08
Approvals Certifications	PCI PTS 5.x   EMV L1/L2   payWave   PayPass   ExpressPay D-PAS   Interac Flash J-Speedy   FeliCa   UnionPay UICS   TQM   PBOC L1/L2
ECR interface	KIT via Cloud   KIT API   KIT JSON   KIT TLV   ZVT-LAN